


Introducing the Epson® SureColor® F6070 (44") F7070 (64")



How do you reinvent the dye-sublimation transfer printer? You start by specially designing, from the ground up, every component to work together as one system — from the print head and ink technology, to the printer engine and software. The result? A high-performance dye-sublimation transfer printer designed with extreme reliability for true industrial-level production.

Developed using the latest advancements in performance imaging, this innovative system includes our exclusive MicroPiezo® TFP® print head, along with an all-new dye-sublimation ink technology — Epson UltraChrome® DS. The purpose-built SureColor F-Series allows you to focus on what matters most — more profit.

DS EPSON ULTRACHROME DYE SUB INK	MAXIMUM MEDIA WIDTH	MAX. INK CAPACITY PER COLOR	INCLUDED RIP	PRINT SPEEDS	
				SQ FT/HR	
	64" AND 44"	1.5 LITERS	WASATCH SOFT RIP	High Speed	613
				Production	301
				High Quality	172

4 Colors Standard / 4 Colors Maximum 

DAY TO DAY - JOB TO JOB - YOU CAN RELY ON WESTAR

Ph 719-260-9777
FX 866-432-1713
sales@westarsystems.com

Warehouse / Shipping Address
2295 Busch Ave. Unit 6
Colorado Springs, CO 80904

Billing / Mailing Address
1210 West High Point Lane
Colorado Springs, CO 80904

EPSON SURECOLOR F-SERIES F6070 / F7070

Printing Technology

Advanced MicroPiezo TFP Print Head
Variable-Sized Droplet Technology
Nozzle Configuration: 720 nozzles per color (x4)

Print Direction

Bi-directional and uni-directional

Print Quality

Maximum Resolution: 720 x 1440 dpi
Smallest Droplet Size: 5.3 pl

New Ink Supply System

Epson UltraChrome DS Ink technology
Ink Tank Capacity: 1500 ml
Ink Pack Capacity: 1000 ml
Cyan, Magenta, Yellow, Black

Media Handling

Paper Feed Method: Friction
Auto Take-up Reel Unit: Standard
Roll OD Dim.:

44" model: Up to 5.9 in. core)

64" model: Up to 9.8 in. core)

Roll Core Size: 2.3

Roll Weight: Up to 88.18 lbs (40.0 kg)

Printable Area

300 to 1,117 mm (F6070) – 44"

300 to 1,625.6 mm (F7070) – 64"

Max. Printing Width:

44" model: 1,112 mm (43.8")

64" model: 1,615 mm (63.6")

Margins: 5 mm both sides

Media Thickness: Over 75 gsm

44" model: 0.05-0.08 mm

64" model: 0.08-1.00 mm

Control Panel

2.5" Color LCD: 480 x 240 dpi

Printer Interfaces

Hi-Speed USB 2.0, 100BASE-TX/1000BASE-T

Language

Control Code: Epson ESC/PS

Environmental Conditions

Operating: 59 to 113°F (15 to 45°C)

Recommended: 59 to 77°F (15 to 25°C)

Humidity

Operating: 20 to 80%
(40 to 60% recommended)

Dimensions

F7070: 10.9(V) x 5.0(D) x 5.2(H)

Weight: 500 lb

F6070: 6.6(V) x 3.2(D) x 4.5(H)

Weight: 192 lb

Electrical Requirements

Power Supply:

AC 100 – 240 V 50 – 60 Hz 1.0-0.5 A

Power Consumption:

Operating: Approx. 65 W

Ready: Approx. 20 W

Standby: Approx. 9 W

Acoustic Noise Level

Approximately 59 dB(A) according to ISO 7779

Printer Software

Communication Driver
User and Setup Guides
Epson LFP RemotePanel 2
EpsonNet Setup
EpsonNet Config
EpsonNet PrintOptions

Front-end RIP Workflow by Wasatch

F6070: Wasatch SoftRip Included

F7070: Wasatch SoftRip TX Included

Epson UltraChrome DS Ink

Ink Packs	1000 ml
Black	T741100
Cyan	T741200
Magenta	T741300
Yellow	T741400

Epson Limited Warranty and Service

Standard one-year on-site

Accessories

Heavy Roll Media System (Optional) on 64"
Input / Output roll media diameter Up to 11.8"
Input / Output roll media weight Up to 175 lb

Better Products for a Better Future™
www.epson.com

1 The SureColor F-6070 and F-7070 are designed to use only Epson ink packs and not other brands of new or refilled cartridges, or other brands of ink or bulk ink systems. Using Epson cartridges is important for reliable performance and high image quality. Epson offers voluntary recycling of spent ink cartridges.

2 Print speeds are based on print engine speed only. Total throughput times depend upon front-end software, file size, printer resolution, networking, length and width of the print job and frequency of jobs.